

"CLICSLATS"

Privacy, Wind Break & Sand Control Slats

"CLICSLATS" are extruded from virgin high density polyethylene into hollow rectangular tubes which are inserted into the weave of chain link fabric

Material Specifications:

Property	Value
* Density	951 / 956
* Melt Index	24 / 40
* Low Temperature Brittle Point	76 deg F
* Tensile Strength	3700-3850 psi
* Resistance to continuous heat	250 deg F

Dimension

Width	: 28.5mm	+/-0.9mm
Depth	: 8.25mm	+/-0.635mm
Wall Thickness	: 0.76mm	+/-0.076mm
Colour	: Green, white, brown & blue	

Places of Usages:

- * Hotels
- * Gardens
- * Airport
- * Tourist Area
- * Holiday Resorts
- * Tennis & Badminton Courts
- * Swimming Pools
- * Boundary site of work areas
- * Inside factories for demarcation
- * To cover dirty areas / junkyards
- * Storage areas of Industrial plants
- * Car storage yards
- * Play Grounds & Sports stadium
- * Recreational facilities
- * Hospitals
- * Chalets

Advantages:

- * Proven by experts to be a very effective sand and wind control barrier.
- * Easy to install, no special tools or experience required.
- * Has ultra violet inhibitor formulated to retard harmful effects of sunlight.
- * Available in many colours.
- * Adds privacy and beauty to both sides of the fence.
- * Vandal proof.
- * Durable and long lasting.
- * Virtually maintenance free.
- * It can be easily inserted in any existing fence.



CLIC National Industries

General Trading & Contracting Co. K.S.C. (Closed)

P. O. Box 24387 Safat, 13104 Kuwait.

Tel: (965) 24748514/24738742 Fax: (965) 24768994 / 24768165

Email: clic@clicq8.com - Web: www.clicq8.com